

Global Series Closure [Dome Type]

GP8



Example of use: The product does not include cables or cords other than the module.

✓ Features

- >> High density dome type closure with compact size
- >> 288f single splice capacity
- >> Capacity for 2 main cables and max. 6 branch joints, or 24 round type drop cables, or 48 flat type drop cables
- >> Easy cable sealing with reusable mechanical sealing system
- >> Easy mounting on and removal from pole or wall by snap on mounting kit

Product name	GP8	
Installation	Underground or Wall/Poll mount	
Applicable fiber	Single fiber	12-fiber Freeform Ribbon™
Splice capacity	288 fibers	576 fibers
Number of splice per tray	24 splices per tray	4 splices (48 fibers) per tray
Number of port	8 ports	
Cable entry capacity	Main 2 cables, Branch 6 cables or 24 round drop cables or 48 flat drop cables	
Applicable cable diameter	Main Cable ϕ 8-20mm, Branch cable ϕ 8-20mm Round Drop ϕ 3,5-7,5mm, Flat Drop 1.8-2,5x 3,0-4.5mm	
Operating temperature	-20 - +60° C	
IP rating	IP68	
Dimension	280(W)X214(D)X317(H)mm	
Weight	Approx. 4.0kg	

CONTACT US :

Sumitomo Electric Industries, Ltd.
1-3-13,Motoakasaka,Minato-ku, Tokyo 107-8468,Japan
<https://global-sei.com/fttx/>