

Global Series Closure [Dome Type]

GP4-424/GP4-412



Example of use: The product does not include cables or cords other than the module.

Features

- >> Compact and light weight closure
- >> 96f single splice capacity for GP4-424, 72f single splice capacity for GP4-412
- >> Capacity for 2 main cables and max. 4 branch joint or 16 round type drop cables, or 32 flat type drop cables
- >> Easy cable sealing with reusable mechanical sealing system
- >> Easy mounting on and removal from pole or wall by snap on mounting kit

Product name	GP4-424	GP4-412
Installation	Underground or Wall/Poll mount	
Splice capacity (Single fiber)	96 fibers	72 fibers
Number of splice per tray	24 splices	12 splices
Cable entry capacity	Main 2 cables, Branch 4 cables or 16 round drop cables or 32 flat drop cables	
Applicable cable diameter	Main Cable ϕ 5-12mm or ϕ 10-16mm, Branch cable ϕ 8-20mm Round Drop ϕ 3,5-7,5mm, Flat Drop 1.8-2,5x 3,0-4.5mm	
Operating temperature	-20 - +60°C	
IP rating	IP68	
Dimension	205(W)X155(D)X275(H)mm	
Weight	Approx. 3.0kg	

CONTACT US :

Sumitomo Electric Industries, Ltd.
1-3-13,Motoakasaka,Minato-ku, Tokyo 107-8468,Japan
<https://global-sei.com/fttx/>