



DESCRIPTION

The optical fiber cleaver is available with a single fiber adapter for 0.25/0.9/3.0mm fiber. It is a simple operation for the user to remove or install the single fiber adapter and alternate between mass and single fiber cleaving.

FEATURES

- The average cleave angle: $\leq 0.6^\circ$
- Blade cut points: 24
- Blade cut points life: 2000 times/points
- Blade Life: 2000*24 points
- Cleave length: 9-24mm
- Blade diameter: 22mm
- Coating Diameter: 125 μ m
- Size: 94W*75D*61H(mm)
- Weight: 350g
- Material: Stainless steel 402

APPLICATION

- Cutting Fiber

SPECIFICATIONS

Model	OFC-48K-03-C
Suitable Fiber	Single fiber
Mode	Semiautomatic
Fiber Type	0.25/0.9/3.0mm fiber
Coating Diameter	125 μ m
Cleave Length	9~24mm
Cleaving Angle	$\leq 0.6^\circ$
Blade Life	>48000 times
Weight	350g
Dimension	94W*75D*61H(mm)

ORDERING INFORMATION

Part No	Description
OFC-48K-03-C	Basic Single Fiber Cleaver with Fiber Collector
AX-48K-CB-03-06	Blade for Cleaver AX-48K-03/06

Remark : For Ribbon Fiber Cleaver, please contact us at sales@kabex.com.my

Note : Specifications are subject to change without prior notice