

## DESCRIPTION

Designed specifically for housing passive equipment, these special pedestals feature direct-bury bases with a high rib design that do not require stakes for installation. The direct-bury pedestal bases result in a more uniform and secure installation and are less likely to lean or tilt. Auto-locking cover security feature ensures that the pedestals lock properly without requiring key and special alignment but just by pushing and pressing.

## FEATURES

- 8" round profile provides maximum workspace and bend radius provisions for all passives, cables and connectors
- Round pedestal style maintains a consistent look with legacy pedestals in the field
- Constructed of durable, high-strength HDPE materials for maximum security and long service life
- Universal equipment mounting bracket facilitates installation standardization and reduces inventory
- Optional stake mounting provision for joint trench or other special applications
- Color code: green RAL 6019
- Floor mounting kit with its accessories are designed to attach and secure the enclosure to the plinth.
- The mounting kits are only accessible from the inside of the enclosure when in the opened position.
- Universal key for all enclosures



## SPECIFICATIONS

Base Dimensions (mm)	280 x $\Phi$ 250
Whole Dimensions (mm)	650 x $\Phi$ 250
Weight (kg)	4
Working Temperature (°C)	-40 to +65
Insulation Resistance	$\geq 2 \times 10^4 \text{ M}\Omega$
Protection Class	Passed IP54 (IEC 60529)

## ORDERING INFORMATION

Part No.	Description
AX-002	FDP PEDESTAL ENCLOSURE (Without FDP)
AX-002-143-FDP-W118	FIBER DP PEDESTAL CW SP 1X1:8
AX-002-143-FDB-W218	FIBER DP PEDESTAL CW SP 2X1:8
AX-002-143-TFDP	FIBER DP W/O SPLITTER PEDESTAL (Tie FDP)